EAST Search History

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1	"200246370"	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 12:58
L2	1	Rubendall.in. and 707/103	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 12:58
L3	20	Rubendall.in.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:29
L4	24826	707/100 or 707/103R or 707/103Y or 707/102 or 707/104.1	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:29
L5	0	4 and (convert$3 same (dimensional near2 model) same (object-relational near2 model))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:30
L6	1	4 and ((dimensional near2 model) same (object-relational near2 model))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:30
L7	100	4 and ((object-oriented) same (cube or dimension$))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:31
L8	53	7 and (map$4 same objects)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:31

EAST Search History

L9	2	8 and (create with dimensional)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:31
L10	6	4 and ((creat$2 or generat$2) same (dimensional with mode))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:34
L11	1754	((creat$2 or generat$2) same (dimensional with mode))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:35
L12	12	11 and XML	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:32
L13	1	12 and (relationship same descriptions same objects)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:33
L14	638	(relationship same descriptions same objects)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:33
L15	8	(relationship same descriptions same objects) and ((cube or dimensional) near2 (model or schema))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:34
L16	0	15 and 4	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:34
L17	0	4 and ((creat$2 or generat$2) same (dimensional with mode)).clm.	US-PGPUB	OR	OFF	2007/09/14 13:35

L18	63	((creat$2 or generat$2) same (dimensional with mode)).clm.	US-PGPUB	OR	OFF	2007/09/14 13:35
L19	0	18 and (object-relational near2 (schema or model)).clm.	US-PGPUB	OR	OFF	2007/09/14 13:35
L20	141	((creat$2 or generat$2) same (dimensional with mode)).clm.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 13:35
L21	0	20 and (object-relational near2 (schema or model)).clm.	US-PGPUB	OR	OFF	2007/09/14 13:36
L22	0	20 and (object-relational).clm.	US-PGPUB	OR	OFF	2007/09/14 13:36
L23	339	4 and ((creat$2 or generat$2) with (cube or (dimension$2 with (schema or model or structure))))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 14:13
L24	0	23 and (map$3 same object-oriented)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 14:13
L25	6	23 and (map$3 same objects same class)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 14:13
L26	17663	((creat$2 or generat$2) with (cube or (dimension$2 with (schema or model or structure))))	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 14:13
L27	25	26 and (map$3 same object-oriented)	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 14:13
L28	1	26 and 6	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	OFF	2007/09/14 14:13

Sign in

Google

create dimensional model based on descriptio [Search]   Advanced Search
Preferences

The **"AND"** operator is unnecessary -- we include all search terms by default

Web   Scholar   Results **1 - 10** of about **65,300** for <u>create **dimensional model based** on **descriptions** of objec</u>

<u>Scholarly articles for **create dimensional model based on descriptions of objects and object-relational data model and class of object**</u>

<u>Logical foundations of object-oriented and frame-**based** ...</u> - Kifer - Cited by 1061
A <u>**data model** and **data** structures for moving **objects** ...</u> - Forlizzi - Cited by 178
<u>Towards Heterogeneous Multimedia Information Systems: ...</u> - Carey - Cited by 311

[PDF] **Object**-Oriented **Data Model** for **Data** Warehouse
an approach **based** on **Object**-Oriented Paradigm. In this research **Object**-. Oriented **Data**
Model is used for **description** of **Data** Warehouse **data** and basic ...
www.springerlink.com/index/XGQM2VMPW9K7XQP5.pdf - <u>Similar pages</u>

<u>Automatic generation of a **dimensional model** for online analytical ...</u>
20 illustrates a **dimensional model** that corresponds to the example **object-relational data**
model, and was illustratively inferred **based** on the **data** organized ...
www.freepatentsonline.com/EP1473640.html - 86k - <u>Cached</u> - <u>Similar pages</u>

[PDF] <u>Microsoft PowerPoint - Spatial Databases</u>
File Format: PDF/Adobe Acrobat - <u>View as HTML</u>
Object-based Data Models. Based on **objects** or entities ... **Creating** persistent **objects** –
Class. Persistent **Object** .... 2003, -- 2-**dimensional** polygon ...
www.spatial.maine.edu/~beard/Lectures510/Spatial%20Databases.pdf - <u>Similar pages</u>

<u>**Object-relational** mapping @ SharpToolbox - .NET tools, libraries ...</u>
Description:, **Object-relational** mapper and **data** access layer. Dali is self-configuring,
analyzing your database and **object model** and dynamically **creating** ...
sharptoolbox.com/categories/**object-relational**-mappers - 158k - <u>Cached</u> - <u>Similar pages</u>

<u>Software Development Articles-Articles Directory - **Data** Modeling</u>
For example, you can use **data models**, CRC **models**, UML **class** diagrams, ... This
document describes general concepts needed for **object-relational** mapping. ...
www.softdevarticles.com/modules/weblinks/viewcat.php?cid=21 - 70k -
<u>Cached</u> - <u>Similar pages</u>

[PDF] <u>Cell Tuple **Based** Spatio-Temporal **Data Model**: An **Object** Oriented ...</u>
object-based data models increases the complexity of the **data** .... Each **class** has
AttributeID and. **description** (attributes). ...
portal.acm.org/ft_gateway.cfm?id=320140&type=pdf&coll=GUIDE&dl=GUIDE -
<u>Similar pages</u>

[PDF] <u>Two-**dimensional** Software Development **Model** Combining **Object** ...</u>
More detailed **descriptions** of. **object relational model** are given in [9]. .... **Based** on the
formal specification. of each **class**, we perform **data** refinement ...
portal.acm.org/citation.cfm?doid=272263.272284 - <u>Similar pages</u>
[<u>More results from portal.acm.org</u>]

[PDF] <u>Metadata for **Object-Relational Data** Warehouse</u>
File Format: PDF/Adobe Acrobat - <u>View as HTML</u>
advantage of the extended relational **model**. 3 **Object-Relational** Database .... and to
create new materialized views **based** on this. **data**. 4. Metadata: ...

www.ifs.tuwien.ac.at/ifs/general_information/people/tjoa/pub_pdf/tha_dmdw00.pdf -
Similar pages

EP1473640 Microsoft european software patent - Automatic ...
Creating BI entities from the **dimensional model objects** is illustrated by ..... from a group
consisting of a **class** from the **object-relational data model**, ...
gauss.ffii.org/PatentView/EP1473640 - 96k - Cached - Similar pages

Multi-**dimensional data** management system - US Patent 6366922
In the user **object model** for the **object/relational** database system, each **dimension** of
the **data** is associated with a different **class**. FIG. ...
www.patentstorm.us/patents/6366922-description.html - 38k - Cached - Similar pages

1 2 3 4 5 6 7 8 9 10   **Next**

Try Google Desktop: search your computer as easily as you search the web.

---

create dimensional model based on   Search

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

---

©2007 Google - Google Home - Advertising Programs - Business Solutions - About Google

Google

| create dimensional model based on descriptio | | Search | Advanced Search
Preferences |

The **"AND"** operator is unnecessary -- we include all search terms by default. [Details]

Web Results **1 - 10** of about **26,300** for create dimensional model based on descriptions of objects and obje

[PDF] Microsoft PowerPoint - Spatial Databases
File Format: PDF/Adobe Acrobat - View as HTML
Object-based Data Models. Based on **objects** or entities ... **Creating** persistent **objects** –
Class. Persistent **Object** .... 2003, – 2-**dimensional** polygon ...
www.spatial.maine.edu/~beard/Lectures510/Spatial%20Databases.pdf - Similar pages

Object-relational mapping @ SharpToolbox - .NET tools, libraries ...
Description:, Object-relational mapper and **data** access layer. Dali is self-configuring,
analyzing your database and **object model** and dynamically **creating** ...
sharptoolbox.com/categories/**object-relational**-mappers - 158k - Cached - Similar pages

[PDF] Metadata for **Object-Relational Data** Warehouse
File Format: PDF/Adobe Acrobat - View as HTML
advantage of the extended relational **model.** 3 **Object-Relational** Database .... and to
create new materialized views **based** on this. **data.** 4. Metadata: ...
www.ifs.tuwien.ac.at/ifs/general_information/people/tjoa/pub_pdf/tha_dmdw00.pdf -
Similar pages

Comp.**Object** FAQ Version 1.0.9 (04-02) Part 7/13
Odapter Technical **Data Object/Relational** Adapter A Productivity Tool for Scalable ...
Odapter **Object Model** The Odapter **object model** is **based** on three key ...
www.faqs.org/faqs/**object**-faq/part7/ - 56k - Cached - Similar pages

[PDF] An **Object-Relational** Approach to the Representation of Multi ...
temporal **dimension** in a spatio-**object-relational model.** The first approach is **based** on.
extending each relation storing spatial **data objects,** ...
www.springerlink.com/index/vr57hd88rwxrpjd3.pdf - Similar pages

[PDF] Visual Query and Analysis Tool of the **Object-Relational** GIS Framework
User defined schemas are stored in the Metadata Repository ... GinisNT **data model** is
based on **object**-oriented paradigm and. supports common **object**-oriented ...
portal.acm.org/ft_gateway.cfm?id=354836&type=pdf&dl=ACM&dl=ACM - Similar pages

1 Spatial Concepts
(The only exception is if you need to **create** a **user-defined** coordinate system, ... Spatial
supports the **object-relational model** for representing geometries. ...
download.oracle.com/docs/cd/B14117_01/appdev.101/b10826/sdo_intro.htm - 69k -
Cached - Similar pages

> 1 Introduction to Oracle **Objects**
> You can also **create object** views of existing relational **data** to represent and ... The result
> is an **object-relational model** that offers the intuitiveness and ...
> download.oracle.com/docs/cd/B28359_01/appdev.111/b28371/adobjint.htm - 50k -
> Cached - Similar pages

[PDF] Database Management Systems: Relational, **Object-Relational, and ...**

File Format: PDF/Adobe Acrobat - View as HTML
the **object**-oriented **data model.** These four **data models** at the same time ...... structures,

or to **create** indexes **based** on functional values (e.g. to **create ...**
www.cit.dk/cot/reports/reports/Case4/05-v1.1/cot-4-05-1.1.pdf - Similar pages

[PDF] **Object-Relational** Representation of a Conceptual **Model** for ...
File Format: PDF/Adobe Acrobat - View as HTML
TDW design into the conventional ER and an **object-relational models**. ..... Further, since
structured **user-defined** types are analogous to **class** declarations ...
code.ulb.ac.be/dbfiles/MalZim2006ainproceedings.pdf - Similar pages

1 2 3 4 5 6 7 8 9 10   **Next**

Download Google Pack: free essential software for your PC

| create dimensional model based on | Search |

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

---

©2007 Google - Google Home - Advertising Programs - Business Solutions - About Google

Google

| create dimensional model based on descriptio | Search | Advanced Search |
| | | Preferences |

The **"AND"** operator is unnecessary -- we include all search terms by default [details]

Web Results **1 - 10** of about **23,900** for **create dimensional model based** on **descriptions** of **objects** and **obje**

Object-relational mapping @ SharpToolbox - .NET tools, libraries ...
Description:, **Object-relational** mapper and **data** access layer. Dali is self-configuring,
analyzing your database and **object model** and dynamically **creating** ...
sharptoolbox.com/categories/**object-relational**-mappers - 158k - Cached - Similar pages

SharpToolbox category : **Object-relational mapping**
It includes tools to **create** the database schema from the **object model** and .... **Object-
relational** database **mapping**: ActiveRecord, a **data mapping** pattern ...
sharptoolbox.com/Tools.asmx/GetCategory_Rss?category=74089b0a-1105-4389-b1db-
eedf27e20cfb - 61k - Cached - Similar pages

[PDF] Metadata for **Object-Relational Data** Warehouse
File Format: PDF/Adobe Acrobat - View as HTML
advantage of the extended relational **model**. 3 **Object-Relational** Database .... and to
create new materialized views **based** on this. **data**. 4. Metadata: ...
www.ifs.tuwien.ac.at/ifs/general_information/people/tjoa/pub_pdf/tha_dmdw00.pdf -
Similar pages

Comp.**Object** FAQ Version 1.0.9 (04-02) Part 7/13
Odapter Technical **Data Object/Relational** Adapter A Productivity Tool for Scalable ...
Odapter **Object Model** The Odapter **object model** is **based** on three key ...
www.faqs.org/faqs/**object**-faq/part7/ - 56k - Cached - Similar pages

1 Introduction to Oracle **Objects**
The result is an **object-relational model** that offers the intuitiveness and ..... automatic
mapping of **object data** in an Oracle server to program bind ...
download.oracle.com/docs/cd/B28359_01/appdev.111/b28371/adobjint.htm - 50k -
Cached - Similar pages

1 Spatial Concepts
Spatial supports the **object-relational model** for representing geometries. ... A common
example of spatial **data** can be seen in a road **map**. ...
download.oracle.com/docs/cd/B14117_01/appdev.101/b10826/sdo_intro.htm - 69k -
Cached - Similar pages

[PDF] Visual Query and Analysis Tool of the **Object-Relational** GIS Framework
mapping between two **data models**. Therefore, GinisNT is an. **object-relational**
development environment that provides the basic ...
portal.acm.org/ft_gateway.cfm?id=354836&type=pdf&dl=ACM&dl=ACM - Similar pages

[PDF] An **Object-Relational** Approach to the Representation of Multi ...
temporal **dimension** in a spatio-**object-relational model**. The first approach is **based** on.
extending each relation storing spatial **data objects**, ...
www.springerlink.com/index/vr57hd88rwxrpjd3.pdf - Similar pages

[PDF] **Object-Relational** Representation of a Conceptual **Model** for ...

File Format: PDF/Adobe Acrobat - View as HTML
SQL:2003 standard under the name of **object-relational model** [10]. Another approach for

logical-level design of TDBs is **based** on **mapping**. conceptual **models**. ...
code.ulb.ac.be/dbfiles/MalZim2006ainproceedings.pdf - Similar pages

[PDF] Database Management Systems: Relational, **Object-Relational**, and ...
File Format: PDF/Adobe Acrobat - View as HTML
Smart large **objects** can be used to store **user-defined data** types such as ...... whereas
the **Object/Relational mapping** is a mapping of the database **model** to ...
www.cit.dk/cot/reports/reports/Case4/05-v1.1/cot-4-05-1.1.pdf - Similar pages

1 2 3 4 5 6 7 8 9 10   **Next**

Try Google Desktop: search your computer as easily as you search the web.

| create dimensional model based on | Search |

Search within results | Language Tools | Search Tips | Dissatisfied? Help us improve

---

©2007 Google - Google Home - Advertising Programs - Business Solutions - About Google